

Technical Bulletin 202

Mi-Glow® Underwater 528

Mi-Glow® Underwater 528 is red particles which are used in visible light, black light and blue light, pre-mixed with a powdered Wetting Agent for use in underwater inspection. The particles are finer and lighter, allowing them to remain in suspension longer and enhance finer discontinuities. Designed for use in a variety of underwater inspections, including offshore structural welds, pipeline inspection, ship husbandry and to enhance underwater photography.



Properties

Particle Color: Fluorescent Orange/Red

Specific Gravity: 0.4 g/ml

Light Source: Daylight fluorescent under visible light sources (recommend ≥ 200 ft candles), fluoresces in black light and blue light.

Particle Size: Not less than 98% passage through US Standard No. 325 (45 μm) sieve.

Sensitivity: Mi-Glow® Underwater 528 offers the capability of enhancing finer defects with its sieve size. Eighty percent (80%) of Mi-Glow® Underwater 528 particles are less than 15 μm in diameter.

Temperature Limits: 32-120°F (0-49°C)

Shelf Life: Four (4) years, when closed containers are stored in a clean, dry environment away from excessive heat or cold. A Certificate of Shelf Life is available upon request.

Directions for Use

Preparation: It is suggested that Mi-Glow® Underwater 528 be added to water at a concentration of 2 oz. av. Weight to one US gallon of water (15 grams per liter of water). The preparation may vary due to customer practice and specific application. The storage reservoir should have mechanical or air agitation to help keep the particles in suspension.

Particle concentration adequacy is recommended to be checked by a magnetic field indicator or by observation of particles applied to a magnetization device (i.e., electromagnet yoke leg).

When these particles are used in a salt water environment, a fresh batch solution should be made daily to prevent corrosion of the particles.

Further products on request!